



## SEAGUARD® WLR Water Level Recorder

The new Aanderaa SeaGuard WLR is a robust instrument based on the SeaGuard Platform. It is a self contained instrument for measuring tide and temperature. The instrument can be used as a platform for additional measurements (e.g. CTD, current, dissolved oxygen and turbidity).

### Features of the SeaGuard WLR:

- High Resolution and low drift
- Low maintenance needs
- Selectable interval from 2 seconds to 2 hours
- SeaGuard Studio visualization software
- Smart sensor topology based on a reliable CANbus interface (AiCaP)
- Output parameters: Pressure, Temperature, Tide pressure, Tide level. The WLR also provides raw data of the Pressure and Temperature measurements.
- Real-Time XML Output on RS-422(optional)
- For use in sea and fresh water
- Windows CE based datalogger with TFT colour touch panel for configuration
- 3 pressure ranges:
  - 0 - 400 kPa / ~30m depth
  - 0 - 700 kPa / ~60m depth
  - 0 - 3100 kPa / ~300m depth

SeaGuard Water Level Recorder measures hydrostatic pressure based on a silicon pressure sensor 4647. The pressure measurements are sampled and temperature compensated by an advanced Digital Signal Processor.

The SeaGuard WLR application areas are in fixed installations, either deployed in a seabed installation in shallow waters, or mounted onto a fixed structure in the upper water column. Typical applications for the sensor are measurements of tide in Ports and Harbors, Marine operations, Hydrography, Weather forecast, and Climate studies.

The tide measurement is an average of the hydrostatic pressure measured over a time period of 10 seconds to 8 minutes (Integration time configurable by the user). The update interval is between 2 seconds and 2 hours.

The SeaGuard WLR output parameters are Tide pressure, Tide level, Pressure and Temperature. Tide levels are preliminary, internally calculated estimates, based on fixed, user selectable values of atmospheric pressure and water salinity. Compensation for actual atmospheric pressure and salinity can be postprocessed if such data is available. Tide pressure is an average of hydrostatic pressure over the integration time.

Since all calibration and temperature compensation data are stored inside the sensor, the parameters are by default presented directly in engineering units without any external calculation. The WLR also provides raw data of the pressure and the temperature measurements.

The output parameters from the SeaGuard WLR are easily presented in SeaGuard Studio.

The SeaGuard WLR and the Aanderaa smart sensors are interfaced by means of a reliable CANbus protocol (AiCaP) using XML for plug and play capabilities. The smart sensors can be mounted directly on the top end-plate or connected via cable to an Aanderaa SeaGuard and are automatically detected and recognized.

The SeaGuard WLR can be used with Aanderaa Real-Time Collector for real-time data.

The SeaGuard WLR has 2 battery compartments for long deployment time.

The SeaGuard WLR can be equipped with a Conductivity sensor for calculation of Salinity, Density and Sound of speed.

**Top-End Plate:** Multiparameter platform  
**Recording system:** Data Storage on SD card  
**Storage Capacity:** ≤ 4GB  
**Battery:** 2 batteries inside the instrument  
     Alkaline 3988 9V, 15Ah (nominal 12.5Ah; 20W) down to 6V at 4°C)  
     or Lithium 3908: 7V, 35Ah  
**Supply voltage:** 6 to 14Vdc  
**Operating temperature:** -5 - +40°C (23 - 104°F)  
**Deployment depth:** Up to 300 m depending on sensor (see sensor specification)  
**Dimensions:** OD: 139mm H: 356mm  
**Weight in air:** 6.0kg  
**Weight in water:** 1.5kg  
**Materials:** PET, Titanium, Stainless Steel 316, Epoxy

**Average current drain(@ 9V):** Tidal average period of 40s  
*Note! The instrument will calculate and present the average current drain based on the configuration, refer to TN 320.*

Output Interval: freq.	2 sec	1 min	10 min	30 min
2 Hz:	25.1 mA	5.0 mA	1.4 mA	1.2 mA
4 Hz:	25.1 mA	5.0 mA	1.4 mA	1.2 mA

**Tide sensor specifications:**

**Pressure:**  
 4647A Range: 0 - 400kPa (58 psia) ~ 30m depth  
 4647B Range: 0 - 700kPa (101 psia) ~60m depth  
 4647C Range: 0 - 3100kPa (449 psia) ~300m depth  
**Resolution:** 0.0001% FSO  
**Accuracy:** ±0.04% FSO  
**Pressure connection:** Swagelok™ 1/8 inch  
**Inlet port (reference):** top of the pressure port  
**Pressure parameters:** Pressure in kPa, Pressure raw data in LSB  
**Temperature:**  
 Range: 0 - 36°C (32 - 96.8°F)  
 Resolution: 0.001°C (0.0018°F)  
 Accuracy: ±0.4°C (0.72°F)  
 Response Time (63%): < 2 min  
 Temperature parameters: Temperature in °C, Temperature raw data in LSB  
**Tide:**  
 Integration time: 10s - 8 minutes  
 Tide parameters: Tide pressure in kPa, Tide level in meter

**ACCESSORIES included:**

SeaGuard Studio  
 SD card: 2 GB  
 1 Alkaline Battery 3988  
 Documentation on CD  
 Carrying handle 4132

**ACCESSORIES not included:**

SD card with capacity up to 4GB  
 Electrical terminal 4784  
 Mooring frame 5031, 5031A  
 In-line mooring frame 4044  
 Internal Lithium battery 3908  
 Internal Alkaline battery 3988  
 Internal battery shell 4513  
 Maintenance kit 3813  
 Tools kit 3986A  
 Real-Time license and Collector 4715  
 Offline configuration software 4811  
 Conductivity sensor 4319, refer D369  
 Temperature sensor 4880, refer D391  
 Oxygen optode 4835, refer D385  
 Turbidity sensor 4112 (analog), refer D377  
 for Current measurements, refer SeaGuard RCM (D368)  
 for Wave and Tide measurements, refer SeaGuard WTR (D386)

*Specifications subject to change without prior notice.*

## Aanderaa Real Time

The data message from the instrument is in XML format. A user application can access the Aanderaa Real-Time Collector over the Internet or Intranet. Each user application will experience an individual connection to the instrument data due to a queue management system in the collector. One licence per SeaGuard instrument serves multiple user applications. Including Aanderaa Real-Time Collector, Aanderaa Real-Time Viewer, Style Sheets and example application (refer B163).

## Offline Configuration

The Seaguard Offline Configuration is a PC application used to create and modify configuration files for the SeaGuard. The configuration files can be imported to one or multiple SeaGuard instruments using a compatible memory card (SD card). (refer TD 275).



Visit our Web site for the latest version of this document and more information  
**www.aadi.no**

Aanderaa is a trademark of Xylem Inc. or one of its subsidiaries.  
 © 2012 Xylem, Inc. D387 December 2012

Aanderaa Data Instruments AS  
 Sanddalsringen 5b, P.O. Box 103, Midtun,  
 5828 Bergen, Norway  
 Tel +47 55 60 48 00  
 Fax +47 55 60 48 01