



## PHINS

### FOG-BASED HIGH-PERFORMANCE INERTIAL NAVIGATION SYSTEM

**PHINS** is an inertial navigation system providing position, true heading, attitude, speed, depth and heave. Its high-accuracy inertial measurement unit is based on **iXBlue**'s fiber-optic gyroscope technology coupled with an embedded digital signal processor that runs an advanced Kalman filter.

#### FEATURES

- All-in-one high-accuracy 3D positioning with heading, roll and pitch
- FOG, unique strap-down technology
- Multiple aiding available: (DVL, EM log, GPS, USBL, LBL and depth sensor)
- Compact, light and reliable
- Ethernet, web server (GUI)

#### BENEFITS

- High grade INS performance
- High reliability and maintenance free
- Ease of use and quick installation
- Perfectly silent
- Small power consumption
- Low latency
- Small power consumption

**APPLICATIONS** • Highly demanding civil or defense surface vessels or autonomous underwater vehicles



# PHINS

## TECHNICAL SPECIFICATIONS



IMO Certified  
N° 19110  
N° 19183

### PERFORMANCE

<b>Position accuracy</b>	
With GPS	Three times better than GPS accuracy
With USBL / LBL (subsea applications)	Three times better than USBL / LBL accuracy
With DVL	0.1% of traveled distance (CEP 50)
No aiding for 2 min / 5 min	3 m / 20 m (CEP 50)
Pure inertial mode	0.6 nm / hour (CEP 50)
<b>Heading accuracy</b>	
With GPS	0.01 deg secant latitude RMS <sup>(1)</sup>
With USBL / LBL / DVL (subsea applications)	0.02 deg secant latitude RMS <sup>(1)</sup>
Roll and pitch dynamic accuracy (no aiding)	0.01 deg RMS
Heave accuracy (Smart Heave) <sup>(2)</sup>	2.5 cm or 2.5% RMS

### OPERATING RANGE / ENVIRONMENT

Operating / storage temperature	-20°C to 55 °C / -40°C to 80 °C
Rotation rate dynamic range	Up to 750 deg/s
Acceleration dynamic range	± 15 g
Heading / roll / pitch	0 to +360 deg / ±180 deg / ±90 deg
MTBF (observed)	80 000 hours

### PHYSICAL CHARACTERISTICS

Dimensions (L x W x H)	180 x 180 x 162 mm
Weight in air	4.5 kg
Waterproof	IP66

### INTERFACES

Serial	RS422 or RS232
Ethernet	100 MBit - UDP / TCP server / TCP client / web server (GUI)
Pulse	PPS, Trigger
Inputs / outputs	Configurable 7i / 5o - Pulse <sup>(3)</sup> 4i / 2o - Configuration port
Baud rates	Up to 460 kbaud
Data output rate	0.1 Hz to 200 Hz
Power supply / consumption	24 VDC (20 - 32 V) / < 20 W

(1) Secant latitude = 1/cosine latitude

(2) Whichever is greater for periods up to 30 seconds. Smart heave is delayed by 100 s fixed value  
Real-time heave accuracy is 5 cm or 5% whichever is greater

(3) Use GPS PPS pulse for accurate time synchronization of PHINS